

ON Series

LED Highbay 100W, 150W and 200W



- Replacing to tradition MH, MV and HPS High-bay
- Five steps finishing, super durable TGIC paint material resists all tough weather conditions while providing optimal illuminance (TGIC : Triglycidylisocyanurate)
- Magnesium alloy made hollow heatsink fins to optimize thermal management which get a result in less dust accumulation and LIGHT WEIGHT

More Informations
Visit our website >>



Specifications

Model	Wattage	Luminous Flux	Input Voltage	Power Factor	Temperature Color	CRI	Working Temperature	Life Span	Warranty
KC-HB100N18-A	100	18000 lm	180 - 277 VAC	0.95	3000K/6500K	80 Ra	- 5 to 45 °C	50000 Hrs	5 Years
KC-HB150N18-A	150	27000 lm	180 - 277 VAC	0.95	3000K/6500K	80 Ra	- 5 to 45 °C	50000 Hrs	5 Years
KC-HB200N18-A	200	36000 lm	180 - 277 VAC	0.95	3000K/6500K	80 Ra	- 5 to 45 °C	50000 Hrs	5 Years

Structure Diagram

Model	Diameter (mm)	H (mm)
KC-HB100N18A	Φ245	175
KC-HB150N18-A	Φ280	202
KC-HB200N18-A	Φ290	202

Light Distribution

