

# CS Series

LED Streetlight 60W, 90W, 100W, 120W, 150W, 200W and 250W



- Classic Series housing and heat sink are separate. Suitable for lighting on highways, urban roads and secondary roads, as well as of stadiums, sidewalks, residential areas, industrial areas, squares, parks, schools, villas, gardens and other places.
- ZAG lens technology, 8% light efficiency, higher than similar lights in the market, with higher light transmittance up to 98%.
- High luminous efficiency, >155LM/W

**More Informations**  
Visit our website >>



## Specifications

Model	Wattage	Luminous Flux	Input Voltage	Power Factor	Temperature Color	CRI	Working Temperature	Life Span	Warranty
KC-ST6CS16-A	60	9600 lm	100 - 240 VAC	0.95	3000K/5500K	70 Ra	- 30 to 60 °C	50000 Hrs	2 Years
KC-ST9SCS16-A	90	14560 lm	100 - 240 VAC	0.95	3000K/5500K	70 Ra	- 30 to 60 °C	50000 Hrs	2 Years
KC-ST10CS16-A	100	16000 lm	100 - 240 VAC	0.95	3000K/5500K	70 Ra	- 30 to 60 °C	50000 Hrs	2 Years
KC-ST12CS16-A	120	19200 lm	100 - 240 VAC	0.95	3000K/5500K	70 Ra	- 30 to 60 °C	50000 Hrs	2 Years
KC-ST15CS16-A	150	24000 lm	100 - 240 VAC	0.95	3000K/5500K	70 Ra	- 30 to 60 °C	50000 Hrs	2 Years
KC-ST20CS16-A	200	32000 lm	100 - 240 VAC	0.95	3000K/5500K	70 Ra	- 30 to 60 °C	50000 Hrs	2 Years
KC-ST25CS16-A	250	40000 lm	100 - 240 VAC	0.95	3000K/5500K	70 Ra	- 30 to 60 °C	50000 Hrs	2 Years

## Structure Diagram

Model	L (mm)	W (mm)	H (mm)
KC-ST6CS16-A	399	328	98
KC-ST9SCS16-A	484	328	98
KC-ST10CS16-A	484	328	98
KC-ST12CS16-A	569	328	98
KC-ST15CS16-A	654	328	98
KC-ST20CS16-A	654	328	98
KC-ST25CS16-A	739	328	98

# Light Distribution

